

YBS Insulation

HIGH QUALITY PRODUCTS FOR THE BUILDING INDUSTRY



A Quality Assured Product

Roofers Choice *Light Weight*

High Performance Breather Membrane

Prevents the ingress of wind driven rain and can be used as a temporary roof covering



Roofers Choice is a multi-layer laminate film composite made of Polyolefin materials, resulting in a pitched roof underlay that has high vapour permeability but is also highly water resistant.

Roofers Choice can be installed without the need for roof space ventilation, and is suitable for both Commercial and Domestic buildings, it is the ideal roof underlay for Warm and Cold Pitched Roofs.

Manufactured without the use of CFC's Roofers Choice is 100% recyclable and is very durable with high tensile strength properties. These coupled with excellent UV and heat stability properties ensure a life-span in excess of 30 years.

Roofers Choice breathable membrane has received BBA Approval and complies with BS5534-2003 Code of Practice for slating and tiling and NFRCTB6.

Recommendations for the use of vapour permeable membranes in pitched roofs are contained in BS 5250 : 2002 'Code of practice for control of condensation in buildings'.

Highly Water Resistant

Breathable

Eliminates Roof Space Ventilation

Energy Saving

User Friendly

Made to a Quality System meeting the requirements of BS EN ISO 9002



www.ybsinsulation.com

Roofers Choice

Installation Guide

Non-Ventilation Cold Pitched Roofs (partially supported)

Roofers Choice when installed as a partially supported system should be fixed in the traditional method for roof tile underlays laid parallel to the eaves and **draped between the rafters** to ensure that any moisture reaching the underlay will drain away. It is held in place by the tile battens, fixed using staples or large headed nails. **Roofers Choice** can also be installed by pulling taut from gable to gable provided that a 25mm counter batten is fixed to each rafter.

Prevention of Condensation

The complete roof construction, ceiling boards, underlay, insulation and roof tiles should be considered as a total roof system with regard to condensation risk. Insulation at ceiling level should be pressed tightly into the eaves against the underlay and all penetrations into, and out of, the roof space should be sealed. More extensive details of this can be found in our BBA certificate Section 5.

General

Roofers Choice must be installed with the (Grey) Printed side, face-up and overlapped with the minimum dimensions listed. Trimming is achieved with a sharp knife. When partially supported with a horizontal lap between battens an extra batten should be introduced 25mm above the bottom edge. This will restrain the lap from opening under wind uplift.

Roofers Choice prevents the ingress of wind driven rain and can be used as a temporary roof covering and left exposed to the elements. However it must be installed as recommended in our technical leaflet with regards to overlaps, fixings, draped between rafters or counter-battened and direct contact with uncured treated timber avoided.

Technical Data

Property	Units	Value
Weight	g/m ²	100
Water Vapour Resistance	Sd (M) MN/sg	c.0.02 0.15
Water Vapour Transmission	g/m ² /24 hr	1348
Fire Rating	-	EN13501-1
Exposure Times UV Degregation	-	3/4 months

Product Data

Roll Width (linear metres)	1.0	1.0	1.5
Roll Length	50	25	50
Coverage / roll	50m ²	25m ²	75m ²
Roll Weight	5 Kgs	2.5 Kgs	7.5 Kgs

Technical and Sales Support

For more detailed information please refer to our **Technical Data Sheet, BBA Certification or simply contact Yorkshire Building Services on 01909 721662 Email: technical@ybsinsulation.com**



Yorkshire Building Services (WHITWELL) Ltd Crags Industrial Park, Morven Street, Creswell, Derbyshire, S80 4AJ
Tel: 0844 99 100 44 **Fax:** 0844 99 100 55 **E-Mail:** sales@ybsinsulation.com **Web:** www.ybsinsulation.com

Prevention of Condensation (Extensions)

The roof space environment in both the extension and the original part of the dwelling should be the same. If the original part of the roof is vented then the extension should also be vented. Only if the extension is completely sealed off from the original roof should the VapR-free be installed without the aid of roof space ventilation.

Non-Ventilation Warm Pitched Roofs (fully supported)

Roofers Choice when fully supported by the insulation can be laid vertically or parallel to the eaves and **held in place using counter battens** (minimum height 25mm). These in conjunction with 25 mm tile battens will ensure a minimum 50 mm clear airway above the underlay and will assist natural air movement through the batten space. Battens should be fixed using staples or large headed nails.

Roof space ventilation is not required for warm or cold pitched roofs but ridge or high level ventilation over the roof underlay for tight fitting tiles or slates will assist any moisture vapour to disperse more easily when air temperatures are very low.

Minimum Overlap Details

Roof Pitch	Horizontal Laps		Vertical Laps
	Partially Supported	Fully Supported	Either
12.5 ⁰ to 14 ⁰	225	150	100
15 ⁰ to 34 ⁰	150	100	100
35 ⁰	100	75	100

Detail	Minimum Overlap	
	Horizontally and Vertically (mm)	
Verge	25	
Hips	150	
Ridge	150	
Valleys	300	
Eaves	25	

Technical References

BBA Certification	07/4420
Warm Roofs without Vents	Yes
Cold Roofs without Vents	Yes
Cold Roofs with Vents	Yes
Colour	Light Grey
Nail Tear Strength	
Machine Direction	143
Cross Direction	159

Eaves : YBS Insulation strongly recommend the use of Underlay Support Trays in both open and closed eave construction. Details of this unique versatile product can be obtained directly from YBS Insulation or from one of our stockists.

Packaging and Storage : Roofers Choice is wrapped in polythene and delivered on a pallet. Individual rolls should be stored on their sides on a clean, dry, flat surface and protected from direct sunlight.