



Yorkshire Building Services (Witwell) Ltd.,
The Craggs Industrial Park, Morven Street, Creswell, Derbyshire S80 4AJ
Tel: 01909 721662 Fax: 01909 721442
www.ybsinsulation.com

COSHH Assessment Form

1 MATERIAL

Cavi-Mate' Cavi-Mate is a robust window installation system. Manufactured from high quality PVC-U, it is a window former, locator and cavity closer.

Components & Approximate Proportions - UPVC Extrusion and EPS

2 WORK ACTIVITY

Window former / locator & cavity closer for all reveal types.

3 RISK TO HEALTH

a) HAZARDOUS CONTENTS

Non-Hazardous.

b) ROUTES OF EXPOSURE:

Skin absorption:	Yes	Eyes:	No
Inhalation:	Yes	Ingestion:	No

4 CONTROL METHODS

PROTECTION EQUIPMENT	TYPE TO BE WORN
Goggles/visor	No
Gloves	No
Coveralls	No
Respirator/mask	No
Other	No

5 COSHH ASSESSMENT (estimate of risk to health)

a) Risk to health adequately controlled if above precautions in force

6 COSHH ACTION

1	HANDLING PRECAUTIONS	None
2	MAINTENANCE OF CONTROL MEASURES	None
3	MONITORING OF EXPOSURES	None
4	INFORMATION TO STAFF	None
5	WRITTEN INSTRUCTIONS ISSUED	None
6	TRAINING REQUIRED	None
7	HEALTH SURVEILLANCE	None
8	OTHER CONTROLS	None

7 FIRST AID As specified

Inhalation; If inhalation of large quantities of dust should occur, remove to fresh air and seek medical attention. (Decomposition or combustion products); Possible nausea, dizziness or breathing difficulties If breathing difficulties occur move victim to fresh air and Consult doctor if required.

Skin contact; No known hazard at room temperature. When burning will melt and can adhere to skin. Do not remove melted material -flush with cold water. Cover burns with sterile dressing and obtain medical advice.

8 FIRE ARRANGEMENTS As specified

Material is combustible but not readily ignitable. Avoid breathing smoke. Only fire applies E.P.S. is a combustible material to BS476: Part 4. Type A (flame retardant additive) is specially formulated to restrict the extent of burn when tested to BS4735: 1974 and is classified P, not easily ignitable, when tested to BS476: Part 5: 1979. For fire characteristics and fire performance of X.P.S please refer to BS6203: 1982. Should a fire occur, normal evacuation procedures should be carried out.

Extinguisher type - Water, Dry Powder, carbon dioxide or foam may be used.

9 STORAGE As specified

Store in dry conditions away from other flammable materials.

10 TRANSPORT None

11 SPILLAGE None

12 WASTE DISPOSAL As specified

Scrap UPC-U is not classified as 'notifiable waste' under the Disposal of Poisonous Wastes Act 1972, and may be disposed of by landfill or by incineration in compliance with Local Authority Control of Pollution Act 1974. Material is not biodegradable.



Yorkshire Building Services (Witwell) Ltd.,
The Craggs Industrial Park, Morven Street, Creswell, Derbyshire S80 4AJ
Tel: 01909 721662 Fax: 01909 721442
www.ybsinsulation.com

COSHH Assessment Form

1 MATERIAL

Cavi-Mate Fire Stop' Cavi-Mate Fire Stop is a robust fire retardant window installation system. Manufactured from high quality PVC-U, it is a window former, locator and cavity closer.

Components & Approximate Proportions - UPVC Extrusion and Mineral Fibre

2 WORK ACTIVITY

Window former / locator & cavity closer for all reveal types.

3 RISK TO HEALTH

a) HAZARDOUS CONTENTS:

Hazardous
Mineral Fibres: May cause transient mechanical skin irritation. High dust levels may irritate the throat and eyes.

b) ROUTES OF EXPOSURE:

Skin absorption:	Yes	Eyes:	Yes
Inhalation:	Yes	Ingestion:	Yes

4 CONTROL METHODS

PROTECTION EQUIPMENT	TYPE TO BE WORN
Goggles/visor	yes
Gloves	yes
Coveralls	yes
Respirator/mask	yes
Other	yes

5 COSHH ASSESSMENT (estimate of risk to health)

a) Risk to health adequately controlled if above precautions in force

6 COSHH ACTION

1	HANDLING PRECAUTIONS	None
2	MAINTENANCE OF CONTROL MEASURES	None
3	MONITORING OF EXPOSURES	None
4	INFORMATION TO STAFF	None
5	WRITTEN INSTRUCTIONS ISSUED	None
6	TRAINING REQUIRED	None
7	HEALTH SURVEILLANCE	None
8	OTHER CONTROLS	None

7 FIRST AID As specified

Inhalation; If inhalation of large quantities of dust should occur, remove to fresh air and seek medical attention. (Decomposition or combustion products); Possible nausea, dizziness or breathing difficulties. If breathing difficulties occur move victim to fresh air and Consult doctor if required.

Skin contact; If irritation occurs, wash off under cold running water prior to washing with mild soap. Do not rub or scratch.. When burning will melt and can adhere to skin. Do not remove melted material -flush with cold water. Cover burns with sterile dressing and obtain medical advice.

Ingestion; If irritation occurs, clean throat by rinsing with cold, potable water. If ingested Consult your doctor.

Eyes; If irritation occurs, flush eyes with potable cold water. Do not rub the eyes.

8 FIRE ARRANGEMENTS As specified

Material is combustible but not readily ignitable. Avoid breathing smoke.

Extinguisher type - Water, Dry Powder, carbon dioxide or foam may be used.

9 STORAGE As specified

Store in dry conditions away from other flammable materials Keep material in original packaging until it is to be used. Store material to protect against damage.

10 TRANSPORT None

11 SPILLAGE None

12 WASTE DISPOSAL As specified

Scrap UPC-U is not classified as 'notifiable waste' under the Disposal of Poisonous Wastes Act 1972, and may be disposed of by landfill or by incineration in compliance with Local Authority Control of Pollution Act 1974. Material is not biodegradable.